

G168 v1.1 Design for Extreme Loads

Revision

Rev.	Author	Revised	Released	Date	Notes
Draft	D. Malcolm			2017-2-6	
Review	A. Ojeda			2017-2-6	
Final	K. Wolf			2017-2-6	



Scope

This document describes the methodology used in the design of the G168 v1.1 turbine for extreme loads. It presents in detail the results of the process for some of the critical components including the mast-to-shaft connection, the drive shaft, the blade at the connection to the upper and middle arms, and the connection between the middle arm and the central mast. Results for the support structure are also presented.

Contents

1	Ir	ntrod	uction	. 10
2	Ме	ethod	lology	. 11
	2.1	De	sign load cases	. 11
	2.2	Saf	fety factors	. 11
	2.:	2.1	Partial safety factors for loads	11
	2.:	2.2	Partial safety factors for material strength	11
	2.:	2.3	Margin of safety	11
	2.3	Fin	ite element analysis	. 12
3	Mi	inimu	m margin of safety summary table	. 13
4	Ce	entral	mast	. 15
	4.1	Loa	ad case	. 16
	4.2	Fin	ite element model	. 16
	4.3	Ma	terial Properties	. 17
	4.4	Loa	ads and boundary conditions	. 18
	4.5	Ana	alysis results	. 19
5	Dr	rive s	haft	. 23
	5.1	Loa	ad case	. 23
	5.2	Fin	ite element model	. 23
	5.3	Ma	terial properties	. 24
	5.4	Loa	ads and boundary conditions	. 24
	5.5	Ana	alysis results	. 25
6	Uŗ	oper a	arm-blade connection	. 27
	6.1		ad case	
	6.2	Bra	acket	. 29
	6.7	2.1	Finite element model	29
	6.7	2.2	Material properties	30
	6.3	2.3	Loads and boundary conditions	30
	6.3	2.4	Analysis results	31
	6.3	Pin		. 32



	6.3.	1	Finite element model	.33
	6.3.	2	Material Properties	.33
	6.3.	3	Loads and boundary conditions	.33
	6.3.	4	Analysis results	.35
	6.4	Yok	e	35
	6.4.	1	Finite element model	.35
	6.4.	2	Material properties	.37
	6.4.	3	Loads and boundary conditions	.37
	6.4.	4	Analysis results	.38
7	Blac	des.		41
	7.1	Loa	d case	41
	7.2	Fini	te element model	41
	7.3	Mat	erial properties	43
	7.4	Loa	ds and boundary conditions	43
	7.5	Ana	ılysis results	44
8	Mid	dle a	arm-blade connection	45
	8.1	Loa	d case	46
	8.2	Find	jers	46
	8.2.		Finite element model	
	8.2.	2	Material properties	.48
	8.2.	3	Loads and boundary conditions	.48
	8.2.	4	Analysis results	.51
	8.3	Pins	S	53
	8.3.		Finite element model	
	8.3.	2	Material properties	.54
	8.3.	3	Loads and boundary conditions	.54
	8.3.	4	Analysis results	.56
	8.4	Fing	ger base	56
	8.4.		Finite element model	
	8.4.	2	Material properties	.58
	8.4.	3	Loads and boundary conditions	.58
	8.4.	4	Analysis results	
9	Mid	dle a	arm-mast connection	62
	9.1		d case	
	9.2	Fini	te element model	63
	9.3	Mat	erial properties	64



9.4 Lo	ads and boundary conditions	64
9.5 An	alysis results	66
10 Supp	oort structure	69
10.1 l	_oad cases	71
10.2	Support structure members	72
10.2.1	Finite element model	72
10.2.2	Material properties	75
10.2.3	Loads and boundary conditions	75
10.2.4	Analysis results	77
10.3 E	Bolted joints	81
10.4	Anchors	83
10.4.1	Finite element model	84
10.4.2	Material properties	86
10.4.3	Loads and boundary conditions	86
10.4.4	Analysis results	90
10.5	Caliper bracket	93
10.5.1	Finite element model	95
10.5.2	Material properties	96
10.5.3	Loads and boundary conditions	96
10.5.4	Analysis results	98
11 Refe	rences	. 102
Figures		
Figure 1. G	General arrangement of G168 v1.1	10
Figure 2. L	ocation of the mast-to-driveshaft connection	15
Figure 3. V	iews of the flanged mast-to-drive shaft connection	15
Figure 4. N	Nesh of the mast-to-driveshaft connection	16
Figure 5. N	Nesh of the mast-to-drive shaft connection	17
Figure 6. E	Beam elements and rigid bodies (RB) used to model the bolts	17
	Bending moment applied on the rigid body of the mast side	
_	ixed nodes in the drive shaft end	
	Specified surfaces (red and blue) as bidirectional sliding behaviour	
	Von Mises stress at the mast-to-drive shaft connection	
_	Detail of the Von Mises stress in the vicinity of the bolt hole	
_	Von Mises stress at the mast flange corner	
9410 12.	Total and the mast many control minimum	



Figure 13.	Von Mises stress in the drive shaft	21
Figure 14.	Axial stress in bolts of connection of mast-to-drive shaft	22
Figure 15.	Axial stress in bolts without preload	22
Figure 16.	Detail of the shoulder in the drive shaft	23
Figure 17.	Mesh model of the drive shaft.	24
Figure 18.	Bending moment applied to the drive shaft	24
Figure 19.	Fixed boundary condition in the drive shaft	25
Figure 20.	Von Mises stress in the drive shaft	25
Figure 21.	Detail of the stress concentration in the fillet radius	26
Figure 22.	Volume affected by the negative safety margin	26
Figure 23.	Location of upper and lower arm-to-blade connections	27
Figure 24.	Upper and lower arm-to-blade connection	27
Figure 25.	Parts involved in the load path at upper arm-to-blade connection	28
Figure 26.	Bracket mesh and coordinate system	29
Figure 27.	Bolts modelled as beam elements and rigid bodies (RB)	29
Figure 28.	Pressure loads applied at bracket pin hole due to F_z	30
Figure 29.	Pressure loads applied at bracket pin hole due to M_{y}	31
Figure 30.	Fixed node on each bolt	31
Figure 31.	Factored Von Mises stress in the bracket	32
Figure 32.	Factored axial stress in the bracket bolts	32
Figure 33.	Pin mesh and coordinate system	33
Figure 34.	Pressure load applied at the pin due to F_z	34
Figure 35.	Pressure load applied at the pin due to M_{ν}	34
Figure 36.	Boundary conditions at the pin	35
Figure 37.	Factored von Mises stress in the pin	35
Figure 38.	Finite element model of the yoke	36
Figure 39.	Bolts modeled as beam elements and rigid bodies	36
Figure 40.	Pressure load acting in the yoke due to F_z	37
Figure 41.	Pressure load acting in the yoke due to M_{γ}	38
Figure 42.	Fixed constraint at yoke bolt ends	.38
Figure 43.	Factored Von Mises stress in the yoke	39
Figure 44.	Factored average shear stress in the yoke bolts in Z direction	39
Figure 45.	Factored average shear stress in the yoke bolts in X direction	40
Figure 46	Detail of the upper arm- blade connection	41



Figure 47.	Mesh of the blade	.42
Figure 48.	Laminates modelled with different shell thicknesses	.42
Figure 49.	Bending moment applied to the blade	.43
Figure 50.	Fixed boundary condition at the blade end	.44
Figure 51.	Von Mises stress in the blade section	.44
Figure 52.	Location of the middle arm-to-blade connection	.45
Figure 53.	Exploded view of middle arm-blade connection	.45
_	Components involved in the load path at middle arm-blade connections.	
	Mesh of blade at fingers connection	
	Detail of fingers inserted in blade cells	
	Model of bolted joint between blade and fingers	
Figure 58.	Pressure load for the axial force	.49
Figure 59.	Pressure load for the horizontal bending moment	.49
Figure 60.	Master nodes in the fingers	.50
Figure 61.	Slave nodes in the blade	.50
Figure 62.	Fixed nodes in the upper cut of the blade in orange	.51
Figure 63.	Von Mises stress in the blade	.51
Figure 64.	Von Mises stress in the blade holes at fingers location	.52
Figure 65.	Von Mises stress in the fingers	.52
Figure 66.	Average shear stress in finger bolts	.53
Figure 67.	Mesh view of the finger pin	.54
Figure 68.	Pressure load due to axial force	.55
Figure 69.	Pressure load due to bending moment	.55
Figure 70.	Fixed nodes at the pin surface	.56
Figure 71.	Von Mises stress in the finger pin	.56
Figure 72.	Mesh of the finger base	.57
Figure 73.	Beam elements representing the finger base bolts	.57
Figure 74.	Bearing pressure corresponding to the axial load	.58
Figure 75.	Bearing pressure corresponding to the bending moment	.59
Figure 76.	Fixed boundary condition in the bolt ends of the finger base	.59
Figure 77.	Von Mises stress in the finger base	.60
Figure 78.	Maximum VM Stress due to rigid body in finger base	.60
Figure 79.	Maximum VM Stress due to bearing pressure	.61



Figure 80.	Shear stress in the bolted connection of the finger base	61
Figure 81.	Detail of the middle arm-to-mast connection	62
Figure 82.	Exploded view of the middle arm-to-mast connection	62
Figure 83.	Solid elements to model the arm and the plate	63
Figure 84.	Beam elements used to model the bolts	64
Figure 85.	Loads applied in the arm-to-mast connection	65
Figure 86.	Plate nodes with vertical translation constrained	65
Figure 87.	Bolted joint to mast pieces modelled as rigid bodies	66
Figure 88.	Von Mises stress in the arm-to-mast connection	66
Figure 89.	Detail of maximum von Mises stress in the bolt perimeter	67
Figure 90.	Von Mises stress in the plate	67
Figure 91.	Bolt average shear stress in X direction	68
Figure 92.	Bolt average shear stress in Y direction	68
Figure 93.	Detail of the support structure	69
Figure 94.	Components and machinery involved in the base tower load path \dots	70
Figure 95.	Location of anchors and brake brackets	70
Figure 96.	Radial loads and axial loads	71
Figure 97.	Braking loads applied to the generator platform	72
Figure 98.	Finite element model of the base tower	73
Figure 99.	Shell and beam elements to model the support structure	74
Figure 100). Rigid bodies used to model support structure parts	74
Figure 101	$oxed{1}$. Loads applied in the support structure for the load case DLC 2.3 \dots	75
Figure 102	2. Fixed boundary condition at the leg ends beam elements	76
Figure 103	3. Loads applied to the support structure in the DLC 5.1	76
Figure 104	1. Direct wind force distributed in the support structure	77
Figure 105	5. Von Mises stress in the support structure members for DLC 2.3	78
Figure 106	5. Von Mises stress in the support structure platforms for DLC 2.3 \dots	78
Figure 107	7. Axial forces in the support structure in the DLC 2.3	79
Figure 108	3. Von Mises stress in the support structure members for DLC $5.1 \ldots$	80
Figure 109). Von Mises stress in the support structure platforms for DLC $5.1\ldots$	80
Figure 110). Axial forces in the support structure members for DLC 5.1	81
Figure 111	. Bolted joint detail of middle truss bay	82
Figure 112	Axial forces in the crossing member of middle truss bay	83



Figure	113.	Detail of the connection between the base tower leg and the ancho	
Figure	114.	Anchor plates structure	
Figure	115.	Finite element model of the anchor	85
Figure	116.	Beam elements and rigid bodies in the anchor mesh	86
Figure	117.	Foot numbering with reference to global coordinate system	87
Figure	118.	Loads applied to the anchor using a rigid body element	88
Figure	119.	Fixed nodes at the bolt ends to represent the foundation connection	
Figure	120.	Nodes (in orange) with vertical translation constrained	
Figure	121.	Von Mises stress in the anchor for DLC 2.3	90
Figure	122.	Shear stress in bolt beam elements in Y direction in DLC 2.3	91
Figure	123.	Shear stress in bolt beam elements in X direction DLC 2.3	91
Figure	124.	Von Mises stress in the anchor for DLC 5.1	92
Figure	125.	Shear stress in bolt beam elements in Y direction in DLC 5.1	92
Figure	126.	Shear stress in bolt beam elements in X direction in DLC 5.1	93
Figure	127.	Tensile stress in bolt beam elements in DLC 5.1	93
Figure	128.	Mechanical brake system	94
Figure	129.	Brake bracket detail	94
Figure	130.	Solid element of the bracket	95
Figure	131.	Beam elements of the bracket joint to the platform plate	95
Figure	132.	Factored braking forces applied in the holes for the calipers	97
_		Fixed beam element ends to represent the bolted joint of the brack	
		Nodes (in orange) with vertical translation constrained	
Figure	135.	Factored von Mises stress in the bracket	99
Figure	136.	Factored von Mises stress in corner of vertical and base plates	99
_		Factored von Mises stress in the corner of the horizontal and vertice	
Figure	138.	Bearing stress in the brake bracket plate1	00
Figure	139.	Bolts factored shear stresses in X direction1	01
Figure	140.	Bolts factored shear stresses in Y direction1	01



Tables

Table 1. Minimum margin of safety summary table for structural parts	.13
Table 2. Minimum margin of safety summary table for bolted joints	.14
Table 3. Mesh characteristics of mast-to-drive shaft connection	.16
Table 4. Material properties of the parts involved in the analysis	.18
Table 5. Mesh characteristics of drive shaft modelled	.23
Table 6. Material properties of the drive shaft	.24
Table 7. Mesh characteristics of the bracket	.29
Table 8. Material properties	.30
Table 9. Mesh characteristics of pin	.33
Table 10. Material properties of the pin	.33
Table 11. Mesh characteristic of yoke	.36
Table 12. Material properties of yoke	.37
Table 13. Mesh characteristic of blade	.42
Table 14. Material properties of blade	.43
Table 15. Mesh characteristic of fingers and blade	.47
Table 16. Material properties of blade	.48
Table 17. Mesh characteristics of the finger pin	.53
Table 18. Mesh characteristics of the finger pin	.54
Table 19. Mesh characteristics of the finger base	.57
Table 20. Material properties of the finger base	.58
Table 21. Mesh characteristics of the arm-to-mast connection	.63
Table 22. Material properties of the arm-to-mast connection	.64
Table 23. Loads applied to the support structure	.72
Table 24. Mesh characteristics of the support structure	.73
Table 25. Material properties of the support structure	.75
Table 26. Mesh characteristics of the anchor	.85
Table 27. Material properties of the anchor	.86
Table 28. Reactions in the structure support feet for DLC 2.3	.87
Table 29. Reactions in the structure support feet for DLC 5.1	.89
Table 30. Mesh characteristics of the brake bracket	.95
Table 31. Material properties of the bracket	.96
Table 32. Brake performance characteristics	.96